



NEPOLIN

Interior Emulsion

PLASTIC EMULSION PAINT

One-way interior emulsion paint is premium quality durable emulsion paint. It gives good flow with and leveling with smooth satin finish.

Features

- Smooth Finish
- Washable
- Good opacity
- Egg Shell Sheen

Technical Data

Physical Properties	Specification
Bases	NE1, NE10, NE20
Color Range	Refer to our Color Bazaar Ambience Plus Fandek
Finish	Egg Shell Sheen
*Theoretical Coverage	10-12 sq. meter, per ltr, 2 coats (actual coverage depends surface condition)
Dry Time	30 min (Recoat Time : 3-4 hrs)
Clean Up Solvent	Clean Portable Water
Stability of Diluted Paints	24hrs
Recommended Primer	Pashupati Paints Cement Primer WT/ Interior primer through DTS
Thinning Ratio	Brush or Roller: 1ltr part and 400 ml water by Volume Conventional: 2-3 part paint and 400 ml water (10%) by volume

Application procedure and recommendation for best performance

Surface Type	Step 1	Step 2	Step 3	Step 4
New Surface	Primer (One Coat): Pashupati Cement Primer - ST and/or WT	Putty: Ready Made - Wall Guard Cement Base Putty	Primer (One Coat): Pashupati Cement Primer - ST and/or WT	Finish (2 Coats): Nepolin Interior Acrylic Emulsion
Pre-Painted Prepared Surface	Primer (One Coat): Pashupati Cement Primer - ST and/or WT	Finish (2 Coats): Nepolin Interior Acrylic Emulsion		
Emulsion Painted Prepared Surface	Only if Required	Finish (2 Coats): Nepolin Interior Acrylic Emulsion		

Note: For dark shades, additional cost may apply for complete hiding.

Precaution

- Keep it out of reach of children.
- Stir well and strain before use. Follow safety, health and environmental information.
- Do not apply when ambient temperature is less than 10°C otherwise drying of finish paint will be delayed.
- Do not use any other company's universal strainers or colorants.
- Do not over thin or apply on powdery, chalky or damp surface.
- To avoid premature paint failure, apply finish coats within 24 hours of primer coat.
- Avoid use of plaster of Paris and its mixture to fill dents, gaps and cracks.
- To avoid inconsistency or variation in Color Bazaar shades make sure that base colorants are mixed properly as required.
- It is advisable to apply the paint during dry weather. Application must be avoided in wet and rainy season.

Safety Health and Environmental Instruction

- Container must be kept tightly closed, in a secure, upright position.
- Keep away from source of food, drink, animal feed and children.
- Do not breathe vapour or spray, keep doors and windows open during application.
- Put on air-supply breathing mask while sanding and painting especially in confined space.
- Put on eye glasses for eye protection in case of eye contact, rinse immediately with plenty of water and seek medical advice.
- After application use soap and water or paints – cleaner for hand external body parts.
- Do not dispose paint by throwing in any drain/water channel. Dispose it in a land – fill area only.



Pashupati Paints Pvt. Ltd.

Registered office at Biratnagar, Nepal

Registered Branch office at Kathmandu, Pokhara, Butwal, Nepal

Pashupati Paints
खुशीका रंगहरु

Note

The information is given in good faith but without any warranty. We reserve the right to change the data without prior notice due to continuous R&D.

* Covering capacity is the result obtained on well prepared smooth surface, hence it may change from surface to surface