



# ONE WAY

## EMULSION PAINT

Superior wall finish for interiors

One-way interior emulsion paint is premium quality durable emulsion paint. It gives good flow with and leveling with smooth satin finish.

### Features

- Smooth Finish
- Washable
- Good opacity and coverage
- 100% pure acrylic based emulsun

### Technical Data

Physical Properties	Specification
<b>Bases</b>	OWB1, OWB1A, OWB10, OWB20
<b>Color Range</b>	Refer to our Color Bazaar Ambience Plus Fandek
<b>Finish</b>	Flat Smooth with Soft Sheen
<b>*Theoretical Coverage</b>	11-13 sq. meter, per ltr, 2 coats (actual coverage depends surface condition)
<b>Dry Time</b>	30 min (Recoat Time : 3-4 hrs)
<b>Clean Up Solvent</b>	Clean Portable Water
<b>Stability of Diluted Paints</b>	24hrs
<b>Recommended Primer</b>	Pashupati Paints Cement Primer WT/ Interior primer through DTS
<b>Thinning Ratio</b>	<b>Brush or Roller:</b> 1ltr part and 400 ml water by Volume <b>Conventional:</b> 2-3 part paint and 400 ml water (10%) by volume

### Application procedure and recommendation for best performance

Surface Type	Step 1	Step 2	Step 3	Step 4
New Surface	Primer (One Coat): Pashupati Cement Primer - ST and/or WT	Putty: Ready Made - Wall Guard Cement Base Putty	Primer (One Coat): Pashupati Cement Primer - ST and/or WT	Finish (2 Coats): One-way Acrylic Interior Emulsion
Pre-Painted Prepared Surface	Primer (One Coat): Pashupati Cement Primer - ST and/or WT	Finish (2 Coats): One-way Acrylic Interior Emulsion		
Emulsion Painted Prepared Surface	Only if Required	Finish (2 Coats): One-way Acrylic Interior Emulsion		

**Note:** For dark shades, additional cost may apply for complete hiding.

## Precaution

---

- Keep it out of reach of children.
- Stir well and strain before use. Follow safety, health and environmental information.
- Do not apply when ambient temperature is less than 10°C otherwise drying of finish paint will be delayed.
- Do not use any other company's universal strainers or colorants.
- Do not over thin or apply on powdery, chalky or damp surface.
- To avoid premature paint failure, apply finish coats within 24 hours of primer coat.
- Avoid use of plaster of Paris and its mixture to fill dents, gaps and cracks.
- To avoid inconsistency or variation in Color Bazaar shades make sure that base colorants are mixed properly as required.
- It is advisable to apply the paint during dry weather. Application must be avoided in wet and rainy season.

## Safety Health and Environmental Instruction

---

- Container must be kept tightly closed, in a secure, upright position.
- Keep away from source of food, drink, animal feed and children.
- Do not breathe vapour or spray, keep doors and windows open during application.
- Put on air-supply breathing mask while sanding and painting especially in confined space.
- Put on eye glasses for eye protection in case of eye contact, rinse immediately with plenty of water and seek medical advice.
- After application use soap and water or paints – cleaner for hand external body parts.
- Do not dispose paint by throwing in any drain/water channel. Dispose it in a land – fill area only.



### Pashupati Paints Pvt. Ltd.

Registered office at Biratnagar, Nepal

Registered Branch office at Kathmandu, Pokhara, Butwal, Nepal

**Pashupati Paints**

खुशीका रंगहरु

### Note

---

The information is given in good faith but without any warranty. We reserve the right to change the data without prior notice due to continuous R&D.

\* Covering capacity is the result obtained on well prepared smooth surface, hence it may change from surface to surface